



Smile! CASIO offers practical management solutions for your business



TE-2200
Best For Retail Outlets



TE-2400
Best For Hospitality

■ Electronic Cash Register ■

TE-2200/ TE-2400

Simple yet powerful features and functions increase efficiency of store management and improve productivity

Receipt and journal printer

58mm wide thermal printers equipped with the capability of graphic logo and watermark, double-height printing for receipts, compressed printing mode for journal printing and a printing speed of 14 lines per second. Drop-in paper loading for easy handling of paper replacement.



CASIO SHOP
 NO.34, JLN TANJUNG SD13/1
 BDR SRI DAMANSARA, 52200 KL.
 GST ID: 00098841085
 REG 01-04-2015 13.33
 C 0 1 000036
 CT 1

2 CHINESE HERBS	5	RM24.00
3 FRED RICE	5	RM18.00
1 HARDWARE	5	RM7.50
4 COFFEE	5	RM7.20
1 MIXED RICE	5	RM5.00
1 ELECTRICAL	5	RM15.00
2 STATIONERY	5	RM11.00
4 CAN FOOD	5	RM52.00
1 YONG TAU FOOD	5	RM44.00
2 CHINESE MEDIC	5	RM20.00
21 No		

GST TAX AMT RM154.43
 GST 8% RM9.27

TOTAL RM163.70
 CASH RM200.00
 YOUR CHANGE RM36.30
 TAX INVOICE No. 001268
 PRICE INCLUSIVE OF GST

Display

5.2-inch LCD operator display (2 lines x 16 characters, 7-segment digits for display of amounts) with backlight. Contrast is adjustable for easy readability. Equipped standard with pop-up customer display.



Help function

The blue circle on the keyboard marked as "HELP" can print guidance messages on the receipt printer which contain answers to frequently asked questions such as how to program the time and date. Furthermore, these messages are customizable to meet individual needs.



ENTER NUMBER THEN PRESS <HELP> KEY.

01:HOW TO PROGRAM DATE AND TIME?
 02:UNIT PRICE FOR DEPARTMENTS AND PLUS
 03:HOW TO PROGRAM TAX TABLE?
 04:HOW TO REPLACE

Barcode reading function

The function for direct entry of items not found eliminates the time necessary for searching for new items, thus reducing queues at the register. Items can be added to the master file directly using the associated department name. Direct and batch maintenance functions in the program mode are also available for further processing. The master file can handle newly introduced items according to your program and can be optimized using the inactive items report.

Data storage for your sales reports and program data backup

A CF (Compact Flash) card can be used as a storage device for sales data to create your reports with spreadsheet software to make creating sales reports much easier. A CF card can store program data for backup purposes as well.

Peripherals

Two serial ports are available for direct connection to a PC, external remote printer, modem for connecting to head office, scanner for barcode reading, or slip printer for printing guest receipts or validation.

Table control function

Basic table control function is provided for small restaurants, cafés and bars. External printer can be configured for order or receipt printing.

OTHER USEFUL FUNCTIONS

- Clerk interrupt function
- Scheduler function
- Set menu function
- Backlight turns off automatically when timer is programmed
- Arrangement function
- Memory allocation function

REPORTS

- Financial
- Transaction
- Department
- PLU
- PLU stock
- Table analysis
- Open check
- Monthly
- Hourly
- Flash
- Group
- Clerk
- Time & attendance
- Scanning PLU
- Scanning PLU stock
- Inactive PLU

Z	10-10-2012	21:10		Mode symbol/date/time
C01	MC#01	000045		Clerk descriptor/Mc-No./consecutive No.
Z	SCAN	PLU	0001	Report header/title/reset counter(Z only)
			2001026	Report code
DEPT01		 01	Classified title(by group/dept)
SCAN_PLU001			382	Scanning PLU character/quantity
			17.07%	Sales ratio/total
			#4901234567894	Scanning PLU code
SCAN_PLU002			382	
			38.01%	
			#49889012345674	
SCAN_PLU003			382	
			10.49%	
			#4967890123454	
			1253	Total of this classification
			9,275.83	
DEPT02		 02	
SCAN_PLU010			453	
			1,583.47	
			#4945678901234	
			243	
			10,375.93	
TL			12653	Quantity total
			273,375.93	Amount total

OPTIONS

Model No.	Product
SP-1300	Slip printer
UP-360	External printer
HHS-15	Hand-held barcode scanner

SPECIFICATIONS

Displays	Operator	5.2-inch backlit LCD 2 x 16 characters / 10 digits, 7 segments
	Customer	Pop-up 8-digit numeric LED
Printer	Printing method	Two-station thermal printer
	Printing speed	14 lines/sec. (max.)
	Paper width	58mm +0/-1mm x 80φ
	Paper-loading	Drop-in paper-loading
Memory backup	90-day data backup(vanadium lithium battery)	
Power consumption	AC 120V	Operating 0.5A, Standby 0.1A
	AC 230V	Operating 0.25A, Standby 0.05A
Operating environment	Temperature	0 to 40°C
	Humidity	10 to 85%RH
Dimensions (W x D x H)	400 x 450 x 277mm	
Weight	Approx. 12 kg	

Optional Peripherals



Barcode Scanner



Receipt Printer



CF Card

<http://world.casio.com>

NOTE: Specifications and design subject to change without notice.

CASIO
 CASIO COMPUTER CO., LTD.
 Tokyo, Japan

BW0507-035001A Printed in Japan
 Printed on recycled paper