



# C750 SCANNER

MOBILE - BLUETOOTH - WIRELESS  
- USB - ANDROID - IOS

C750 scanner has the looks to complement the clean design of consumerized devices while comfortably moving with your mobile workers. Its contoured design fits perfectly in the palm. Soft touch plastics, an over-sized trigger button with tactile feedback, and a white LED aimer make scanning easy.



- Prominent Decoding Ability (1D/2D)** - This Wireless Barcode Scanner is equipped with advanced CMOS sensor, which can easily capture 1D/ 2D (QR/ PDF417/ Data Matrix, etc) bar codes from paper and screen, such as computer monitor, smartphone or tablet.
- 3-in-1 Mini Barcode Scanner** - Support Bluetooth Connection, 2.4G Wireless and USB Wired. Connect the scanner to your device via the USB cable. In wired mode, users can scan barcodes while charging.
- Two working mode** - Instant upload mode / storage mode. Internal offline storage supports up to 100,000 barcodes in offline storage
- 3 Trigger Modes** - Manual Scan & Auto-sensing Scan & Continuous Scan. 1200mAh battery ensures 20 hours of continuous handsfree scanning, no pressing the button for efficiency.
- Compatible Operating System** - Easily connected with your laptop, PC, mobile phone, tablet, iphone, ipad, POS. Work with Windows XP/7/8/10, Linux, Mac OS, Android OS, iOS.

| SPECIFICATION         |  |
|-----------------------|--|
| Model Number          | C750 2D BT+Wireless+Wired  |
| Light Resource        | CMOS   |
| Resolution            | 0.3MP (640*480)  |
| CPU                   | 32 bit high resolution   |
| Supported Symbologies | 2D: PDF417, QR Code (QR1/2, Micro), Data Matrix (ECC200, ECC000, 050, 080, 100, 140), Chinese Sensible Code<br>1D : Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code39, Codabar, Code 93, Code 11 |
| Scans Per Charge      | 30000 times  |
| Precision             | ≥ 4 mil (0.10mm)   |
| Decode Speed          | 5 in/s (12.7 cm)   |
| Decode Error Rate     | Less than 1/8 million  |
| Depth Of Scan Field   | Code 39 30mm~180mm(5mil)<br>Ean-13 40mm~380mm(13mil)<br>Data Matrix 30mm~130mm(10mil)<br>QR Code 30mm-155mm (15mil)<br>PDF 417 40mm-125mm(6.67mil)   |
| Print Contrast Signal | ≥ 30°  |
| Scan Angle            | Yaw(Skew)45° & Pitch60°  |
| Working Distance      | 10 meters  |
| Capacity              | 1200mAh  |

| MECHANICAL / ELECTRICAL |  |
|-------------------------|--|
| Working Voltage         | 3.3VDC±5%  |
| Current                 | Working 230mA<br>Standby: 3.4mA (RS232) , 54.0mA (USB) |
| Rated Power Consumption | 186mW  |

| ENVIRONMENT           |              |
|-----------------------|--------------|
| Operating Temperature | (-20°C-45°C) |
| Storage Temperature   | (-20°C-45°C) |
| Humidity              | 5%-85%       |



**Inter-Register Communication (M) Sdn. Bhd. (162895-K)**  
 34, Jalan Tanjung SD 13/1, Bdr Sri Damansara,  
 52200 Kuala Lumpur.  
**Tel:** (6) 03-6272 8000 (8 Line) **Fax:** (6) 03-6272 3210  
 general@irc.com.my  
 www.irc.com.my

**Authorise Resslerer :**