

NEW

OS-214EX / OS-200



The best value entry level desktop printer



The OS series are Argox best-selling printer for 22 years. With more than two million users in worldwide, the OS series are known internationally for their stability and durability.

Application



Laundry



Retail



Healthcare




Assets management

Feature-rich to make daily work simple and easy



Small size fit in tight spaces

Designed for the small working spaces, the OS-214EX / OS-200 is easy to use and operate in tight spaces.



Shell Suit design

Interface roof feature can avoid interface from water spill damage and keep machine close to wall, reduce operating space.



Easy to load ribbon & paper

Print module opening angle up to 110°, the installation of ribbon and paper rolls are easy and convenient.



One hanger for all media

One hanger for 0.5" / 1" / 1.5" media core, increased flexibility, no extra purchase required, support various types of media.

Print Specifications	OS-214EX	OS-200
Printing Method	Direct Thermal & Thermal Transfer	
Printing Resolution	203 dpi (8 dots/mm)	
Printing Speed	Max. 6 ips	
Printing Length	Max. 100"(2540 mm)	
Printing Width	Max. 4.25"(108 mm)	
Memory	32 MB SDRAM, 16MB Flash ROM	
CPU Type	32 bit RISC microprocessor	
Consumables Specifications		
Sensors	Reflective sensor x 1	
Media Type	Roll-feed, die-cut, continuous, fan-fold, black mark, tags, ticket in thermal paper or plain paper	
Media	Max. width: 4.3" (110mm). Min. width: 0.8" (20mm). Thickness: 0.0025"~0.01" (0.0635mm~0.254mm) Max roll capacity (OD): 5" (127mm) Core size: 0.5" (12.7mm) Max roll capacity (OD): 5" (127mm) Core size: 1" (25.4mm) Max roll capacity (OD): 5" (127mm) Core size: 1.5" (38.1mm)	
Ribbon	Ribbon Width: 1"~4"(25.4mm~102mm), Ribbon roll – max OD: 1.45"(37mm), Ribbon Length: Max 92m. Core size – ID: 0.5"(12.7mm) with notch, Wax, Wax/Resin, Resin (Outside and Inside Ribbon)	
Fonts & Symbologies		
Fonts	Internal character sets standard 5 alpha-numeric fonts from 0.049"H ~ 0.23" H (1.25mm ~ 6.0mm) Internal fonts are expandable up to 24x24 4 direction 0 ~ 270 rotation Soft fonts are downloadable Ability to print any Windows True Type font easily. Support scalable font	
1D Barcodes	UPC-A, UPC-E, JAN/EAN, CODE39, CODE93, CODE128, GS1-128 (UCC/EAN128), CODABAR (NW-7), ITF, Industrial 2of5, MSI, UPCadd-on code, POSTNET, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1DataBar Limited, GS1 DataBar Expanded, GS1DataBar Expanded Stacked	
2D Barcodes	QR Code, PDF417 (includingMicroPDF), DataMatrix (ECC200), GS1 DataMatrix, MaxiCode	
Graphics	PPLA: PCX, BMP, IMG, HEX,GDI PPLB: PCX, BMP, Binary raster, GDI PPLZ: GRF, Hex, GDI	
Emulation	PPLA, PPLB, PPLZ	
Interface Characteristics and Integration		
Operation Interface	LED Indicator x 2, Botton(Feed) x 1	
Communication Interface	Ethernet, USB device, RS-232, USB host	USB device
Drivers	Windows Driver for Windows Vista/Win7/Win8/Win10, LINUX Driver, macOS Driver, Raspberry Pi Driver	
Software	BarTender, Printer Tool	
Database Link	Argobar Pro support ODBC Database Connection: Excel, CSV, MS Access, MS SQL, Oracle MySQL, dBASE (*.dbf)	
Operating & Environment Characteristics		
Power Source	Universal Switching Power supply. AC input voltage: 100~240V, 50~60Hz. DC Output: 24V, 2.4A	
Operation Environment	Operation Temperature: 40°F~100°F (4°C~38°C), 0% ~ 90% non-condensing, Storage Temperature: -4°F~122°F (-20°C~50°C)	
Agency Listing	CE, FCC, cULus, CCC, BIS, BSMI, RoHS	
Physical Characteristics		
Printer Dimensions	W 182.5mm x H 173.5mm x D 282mm	
Printer Weight	3.4 lbs (1.54kgs)	



Inter-Register Communication (M) Sdn. Bhd. [198701004225 (162895-K)]

34, Jalan Tanjung SD 13/1, Bdr Sri Damansara,
52200 Kuala Lumpur.
Tel: (6)03-6272 8000 (8 Line) Fax: (6)03-6272 3210
general@irc.com.my
www.irc.com.my

Authorise Resslerer :