

# SRP-275III

3 inch Impact Dot POS Printer



Retail



Hospitality




Banking



Ticketing

# Simply Drop-in



### Built-In Interface

- USB V2.0 FS + Serial + Ethernet\*
- USB V2.0 FS + Parallel
- USB V2.0 FS + Serial
- \* DHCP enabled



**2-color**

### Powerful Printing Performance

- Fast printing speed up to 5.1 lps (at 40 columns) 8.5% faster than competitive models
- High reliability mechanism (18 million lines)
- Two-color printing, quality printing of fonts, graphics



### User-Friendly Design

- Anti-jam technology
- Internal kitchen buzzer & built - in SMPS
- Simply drop-in paper loading
- Stand-alone and wall-mount options



# SRP-275III

3 inch Impact Dot POS Printer

## Specifications

### Print Characteristics

**Print Method**

9 Pin  
Serial Dot Matrix

**Print Speed**

5.1 lps (at 40 columns)

**Print Resolution**

80 dpi (Horizontal)  
144 dpi (Vertical)

**Print Width**

Up to 63.5 mm

**Sensor**

Paper End, Paper Near End, Wall Mounting Paper  
Near End, Rear Cover Open, Black Mark

### Media Characteristics

**Media Type**

Receipt

**Media Width**

76.5 mm

**Media Roll Diameter**

Up to 83 mm

**Media Thickness**

0.06 ~ 0.085 mm

**Supply Method**

Easy Paper Loading

### Physical Characteristics

**Dimensions (WxLxD)**

160 x 239 x 157 mm  
(6.29 x 9.40 x 6.18 inch)

**Weight**

A: 2.4 kg (5.29 lbs.)  
C: 2.5 kg (5.51 lbs.)

**Power**

EnergyStar Certified,  
External Power Adaptor 100-240V AV, 50/60Hz

**Drawer Port**

2 ports (via y-type adaptor)

### Performance Characteristics

**Memory**

64 Mbit SDRAM, 16 Mbit FlashROM

**NV Image Memory**

256 Kbytes (mono)

**Receive Buffer**

64 Kbytes

**User Define Buffer**

64 Kbytes

**Interface**

Max. Triple Interface  
USB V2.0 FS + Serial + Ethernet\*  
USB V2.0 FS + Parallel  
USB V2.0 FS + Serial  
\* DHCP enabled

### Environment Characteristics

**Temperature**

Operating: 0 ~ 40°C (32 ~ 104°F)  
Storage: -20 ~ 60°C (-4 ~ 140°F)

**Humidity**

Operating: 10 ~ 80% RH  
Storage: 10 ~ 90% RH

### Reliability

**Thermal Print Head (TPH)**

300 Million Dots/Wire

**Auto Cutter**

1.5 Million Cuts

### Software

**Emulation**

BXL / POS

**Driver / Utility**

Windows Driver, OPOS Driver, JPOS Driver,  
Linux / Mac CUPS Driver,  
Virtual COM USB/Ethernet Driver, Utility Program

**SDK**

iOS SDK, Android SDK

### Fonts / Graphics / Symbologies

**Character Size**

Font A: 9 x 9 Font B: 7 x 9 KOR: 17 x 9 CHN: 16 x 16

**Characters Per Line**

Font A: 35 Font B: 40 KOR: 20 CHN: 22

**Character Sets**

Alphanumeric: 95  
Extended Graphics: 128 x 27 page  
International: 48

**Graphics**

Supporting user-defined fonts, graphics, formats,  
and logos

### Accessories

**Optional**

Wall Mount, Splash Proof Cover, Ribbon Cartridge,  
B-Melodist, External Buzzer



BR-SRP-275III-EN-MAY16-V1

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.



Inter-Register Communication (M) Sdn. Bhd. [ 198701004225 (162895-K) ]

34, Jalan Tanjung SD 13/1, Bdr Sri Damansara, 52200 Kuala Lumpur.

Tel: (6)03-6272 8000 (8 Line)

Fax: (6)03-6272 3210

Homepage: [www.irc.com.my](http://www.irc.com.my)

E-mail: [general@irc.com.my](mailto:general@irc.com.my)