

XP-Q260III X

Thermal Receipt Printer

Key features

- Quick and easy paper loading
- Triple connectivity:USB+Serial+Lan
- Avoid order missing
- 260mm/s or 200mm/s printing speed can be choose.



Specifications

Model	XP-Q260III X
Printing method	Direct thermal
Printing speed	260mm/s
Paper width	79.5 ± 0.5mm
Paper diameter	80mm
Paper thickness	0.06~0.08mm
Column capacity	384mm dots/ line (58mm) 576 dots/line 512 dots/line (80mm)
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODABAR / ITF / CODE39 / CODE93 / CODE128 QR CODE
Code page	Pc347(Standard Europe) \ Katakana \ PC850(Multilingual) \ PC860(Portuguese) \ Pc863(Canadian-French) \ PC865(Nordic) \ West Europe \ Greek \ Hebrew \ East Europe \ Iran \ WPC1252 \ PC866(Cyrillic#2) \ Pc852(Latin2) \ Pc858 \ IranII \ Latvian \ Arabic \ Pt151(1251)
NV FLASH	256K Bytes
Input buffer	2048K Bytes
Power supply	DC 24V ±2.5A
Cash drawer control	DC 24V ±1A
Interface	Serial+USB+Lan
Auto cutter	Partial
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 10/Linux/OPOS
Command	Compatible with ESC/POS
Gross weight	1.45 kg
Dimension	194.5 × 145 × 147mm (D × W × H)