

PP-9122W



PP-9122W is a fanless modular All-in-One panel PC. It is equipped with RK-3288 processor to operate by Android OS. With MicroSD card slot, memory adding and access is extremely easy!

01/ 22" Fanless Panel PC

AerPPC PP-9122W is an ultra slim modular All-in-One panel PC. It's fanless design offer you a silent and dust free operating environment.

- Platform: Android OS
- Processor: RK-3288 Quad-Core Cortex A17
- System Storage: eMMC
- External Micro SD



02/ Digital Information Signage

No matter using AerPPC or AerMonitor, FEC 22 inch series are beautiful displays with high resolution screens. With universal VESA wall mount design, they can be easily mounted on any flat surface!




03/ Dual Screens, Double Benefit

With FEC unique dual pole, the main panel pc can integrate with a 2nd touch screen when using as a POS system to interact with customers.

All the transaction details & campaign videos / photos can be shown on the screen at the same time!



Specifications



CPU

- RK-3288 Quad Core Cortex A17
1.6Ghz



Storage

- 16GB Built-in eMMC



Speaker

- 2 x 2W Internal Speaker



Touch

- True-Flat PCAP



MTBF

- 50K Hours



OS

- Android 8.1 Oreo




Certification

- FCC / CE Class B



Temperature

- Operation: 0 °C ~ 40 °C (32 °F ~ 104 °F)
- Storage: -20 °C ~ 60 °C (-4 °F ~ 140 °F)




Memory

- 2GB DDR3 On Board



Connection

- WIFI 802.11 ac & BT 4.2 (Optional)



Display

- 22" TFT, 1920 x 1080



Brightness

- 250 nits



Power

- 20V / 90W or 20V / 130W External Adapter



Mounting

- VESA 100 x 100 mm



Appearance

- Aluminum Die-casting + Plastic
- Black with Silver Trim



Dimensions (W x H x D)

- Product: 530 x 338 x 49 mm
- Carton: 652 x 463 x 212 mm



Weight

- Net: 5.7 Kg
- Gross: 7 Kg



Port

- 2 x RJ45 (COM1 & COM2) RS232 with 0V / 5V / 12V
- 3 x USB 2.0; 1 x USB 3.0 (OTG)
- 1 x RJ11 Cash Drawer (12V / 24V)
- 1 x RJ45 GigaLAN
- 1 x Video Port
- 1 x 20V DC Input
- 1 x SD/TF Card Slot (Max: 64GB)
- 1 x Recovery Button



Optional

- 2 x USB 2.0
- 1 x DB9 (COM3)
- 1 x 24V DC Output