

PP-1135



01/ Checking and Monitoring

PP-1135 is a panel PC can use as standalone or mounting in the kitchen.



02/ Need an extra hand?

Let our wall-mount solution be your virtual assistant so you can focus on serving your customer.



03/ Reinvent Your Workflow Efficiency

Our waterproof and industrial grade front panel allows you to seamlessly integrate your POS system closer to the work space than ever before.




04/ FEC ANDROID

FEC provides a complete series of Android POS. From 10" to 22" in for lightweight usage, wall-mount as digital display or with stand for different types of POS terminals.



Specifications



CPU

- Rockchip RK-3568 Quad-core Cortex-A55 up to 2.0GHz



Memory

- 4GB DDR3 On Board



Storage

- 64GB Built-in eMMC




Connection

- WIFI 802.11 ac & BT 4.2 (Optional)



Speaker

- 2 x 2W Internal Speaker



Display

- 15" TFT, 1024 x 768



Touch

- True-Flat PCAP



Brightness

- 350 nits



MTBF

- 50K Hours



Camera

- 2MP Front Camera (Optional)



Power

- 20V / 90W or 20V / 130W External Adapter



OS

- Android 12



Mounting

- VESA 100 x 100 mm



Certification

- FCC / CE Class B



Appearance

- Aluminum Die-casting + Plastic
- Black



Temperature

- Operation: 0 °C ~ 40 °C (32 °F ~ 104 °F)
- Storage: -20 °C ~ 60 °C (-4 °F ~ 140 °F)



Dimensions (W x H x D)

- Product: 366 x 335 x 187 mm
- Carton: 477 x 448 x 307 mm



Weight

- Net: 4.9 Kg
- Gross: 8 Kg



Port

- 1 x 20V DC Input
- 1x RJ45 Gigabit LAN
- 1x Video Port
- 1x RJ11 Cash Drawer (12V or 24V)
- 1 x SD/TF Card Slot (Max: 128GB)
- 1x Recovery button
- 2 x USB 2.0, 1 x USB 3.0, 1 x USB 3.0 (OTG)
- 2x RJ45 (COM1, COM2) RS232 (R1/5V/12V)
- 1 x 12V DC Output

- Side I/O Interface:
1 x USB 2.0



Optional

- Type A: 2 x DB9 (COM3 & COM4) RS232 with 0V / 5V / 12V
- Type B: 1 x PUSB 24V (power adapter request 20V / 130W)
- Type C: 2 x USB 2.0