

PP-8632



AerPPC PP-8632 is an ultra slim modular All-in-One panel PC. It's fanless design offer you a silent and dust free operating environment.

01/ 22" Fanless Panel PC

AerPPC PP-8632 is an ultra slim modular All-in-One panel PC. Its fanless design offer you a silent and dust free operating environment.

- Platform: Intel® Bay Trail
- Processor: Intel® Celeron J1900
- System Memory: DDR3L Standard 4G ; Max 8G



02/ Optional 2nd I/O

FEC offer 4 types of additional I/O options on the nodular main I/O board. With optional 2nd I/O, it creates extra flexibility when purchasing and allows users to fully apply PP-8632 to multiple requirements.



03/ Digital Information Signage

No matter using AerPPC or AerMonitor, FEC 22 inch series are beautiful displays with high resolution screens. With universal VESA wall mount design, they can be easily mounted on any flat surface!




04/ Dual Screens, Double Benefit

With FEC unique dual pole, the main panel pc can integrate with a 2nd touch screen when using as a POS system to interact with customers.

All the transaction details & campaign videos / photos can be shown on the screen at the same time!



Specifications



CPU

- Intel® Celeron J1900 2M Cache, up to 2.42 GHz



Memory

- 4GB Standard, Max 8GB (1 x So-DIMM DDR3L)



Storage

- 1 x 2.5" SATA HDD or SSD



Speaker

- 2 x 2W Internal Speaker



Display

- 22" TFT, 1920 x 1080



Touch

- True-Flat PCAP



Brightness

- 250 nits



MTBF

- 50K Hours



Power

- 12V / 150W External Adapter



OS

- POSReady 7
- POSReady 2009
- Windows 10 Pro
- Windows 10 IoT Enterprise



Mounting

- VESA 100 x 100 mm



Certification

- FCC / CE Class B



Appearance

- Aluminum Die-Casting + Plastic
- Black with Silver Trim



Temperature

- Operation: 0 °C ~ 40 °C (32 °F ~ 104 °F)
- Storage: -20 °C ~ 60 °C (-4 °F ~ 130 °F)



Dimensions (W x H x D)

- Product: 530 x 338 x 49 mm
- Carton: 652 x 463 x 212 mm



Weight

- Net: 5.7 Kg
- Gross: 7 Kg



Port

- 1 x RJ45 (COM1) RS232
- 2 x DB9 (COM2, COM3) RS232
- 4 x USB Type A (3 x USB 2.0, 1 x USB 3.0)
- 1 x PUSB 24V
- 1 x RJ11 (12V / 24V) Supports Two Cash Drawers
- 1 x RJ45 GigaLAN
- 1 x VGA
- 1 x Video

- Side I/O Interface:
1 x USB 2.0 Type A
- Internal Expansion:
1 x Mini PCIe



Optional

- Type A: 2 x RJ45 (COM A, COM B) RS232, 1 x DC-Out 24V, 1 x Mic-in
- Type B: 2 x RJ45 (COM A, COM B) RS232, 1 x PUSB 24V, 1 x Mic-in (Limited Current When Using PUSB 24V)
- Type C: 2 x RJ45 (COM A, COM B) RS232, 1 x PUSB 12V, 1 x Mic-in
- Type E: 2 x RJ11 (12V), 1 x Mic-in
- Type G: 3 x PUSB 12V
- Type H: 1 x PUSB 24V, 2 x 12V (Limited Current When Using PUSB 24V)



Inter-Register Communication (M) Sdn. Bhd. [198701004225 (162895-K)]

34, Jalan Tanjung SD 13/1, Bdr Sri Damansara, 52200 Kuala Lumpur.

Tel: (6)03-6272 8000 (8 Line)

Homepage: www.irc.com.my

Sales Person: (6) 019-337 4781 - Alex Wong

E-mail: general@irc.com.my