


PP-9635



PP-9635B/C


FEC has completely redesigned our newest Panel PCs. AerPPC offers selections of Intel® Celeron®, J1900 processors and features a modular design allowing it to be wall mounted or integrated with a base.

Specifications



CPU

- Intel® Celeron J1900 2M Cache, up to 2.42 GHz



Memory

- 4GB Standard, Max 8GB (1 x 204-pin DDR3L)



Storage

- 1 x 2.5" SATA HDD or SSD



Speaker

- 2 x 2W Internal Speaker



Display

- 15" TFT, 1024 X 768



Touch

- True-Flat PCAP



Brightness

- 350 nits



MTBF

- 50K Hours



Power

- 12V / 90W External Adapter
- 12V / 150W External Adapter



OS

- POSReady 7
- POSReady 2009
- Windows 10 Pro
- Windows 10 IoT Enterprise



Mounting

- VESA 100 x 100 mm



Certification

- FCC / CE Class B




Appearance

- Aluminum Die-Casting + Plastic
- Black with Silver Trim



Temperature

- Operation: 0 °C ~ 40 °C (32 °F ~ 104 °F)
- Storage: -20 °C ~ 60 °C (-4 °F ~ 130 °F)



Dimensions (W x H x D)

- Product: 366 x 334 x 220 mm
- Carton: 480 x 460 x 320 mm



Weight

- Net: 4.9 Kg
- Gross: 8 Kg



Port

- 1 x PUSB 24V
- 1 x RJ11 (12V / 24V) Supports Two Cash Drawers
- 1 x RJ45 (COM1) RS232 with RI / 5V / 12V Selectable
- 1 x VGA
- 4 x USB Type A (3 x USB 2.0, 1 x USB 3.0)
- 1 x RJ45 GigaLAN
- 1 x 12V DC Output

- Side I/O Interface:
1 x USB 2.0 Type A
- Internal Expansion:
1 x Mini PCIe



Optional

- Type A: 2 x DB9 (COM 2, COM 4) RS232 with RI / 5V / 12V Selectable
- Type B: 2 x PUSB 12V,
- Type C: 2 x USB 2.0 Type A