

WINDOW INTERCOM KNDJ-01



KEY FEATURES



High Quality Audio



Rugged AI Construction



Voice Activated Switch

DESCRIPTION


KNDJ-01 is an electronic intercom system which can keep high-fidelity in any window to chat. It adopts United States' most advanced chips with unique design and the stringent quality management.

It reaches the highest standard performance in sound quality, volume, anti-jamming, anti-whistle... It is widely used in bank, hospital, station and soon..

- Window intercom KNDJ-1 Main body with whole aluminum alloy with stainless steel, slave using electroplating plastic shell (triangle slave or metal slave optional).
- The master adopts intercom special loud speaker, and long metal hose microphone (37cm), more convenient to process two-way intercom freely.
- Window intercom KNDJ-1 Main body with whole aluminum alloy with stainless steel, slave using electroplating plastic shell (triangle slave or metal slave optional).
- Streamlined external slave with circular design, make it smart, beautiful and elegant. Internal and external connections using a four-core, high-strength pull-resistant, fully shielded foil line, stronger anti-interference, coupled with the installation of stainless steel which retain more appropriate. (Optional aluminium vice machin eavailable).
- Play fidelity, clear, the volume of inner and outer can be individually adjustable with unique dynamic sound indicator.
- Microcomputer processing circuit with mute function can deal with whistler, echo.
- Recording jack can output both inside and outside voice signals (assist the bankteller system for recording).
- Can be used in those places such as bank, post offices, railway stations, insurance companies, hospitals and other places.

USE FOR VARIOUS OCCASIONS

USE FOR VARIOUS OCCASIONS



SPECIFICATION



INSTALLATION

1. The master is installed in the workplace while the slave out of the workplace. Input the attachment plug of slave into cable jack where the slave connects to the master
2. Connect the transformer to the 220V electric power. DC 12V plug into the power of the master.
3. Switch on the power of master, power indicating red light, said power supply is working correctly.
4. The inside and outside volume knob can separately adjust the volume.

SPECIFICATION

Model No	KNDJ-1
Adapter Input Voltage	110~240V
Operating Voltage	DC 9V
Operating Current	300mA
Output Power	2W + 2W
Microphone Sensitivity	-46dB±2dB 20Hz~16KHz
No Distortion Frequency	100Hz~15KHz
Materials and Technology	High quality aluminium alloy
Dimensions	Host: 11.4*7.8*4.5cm Extension: φ6.7*1.8cm
Packaging	Carton: 46.8cm*35cm*59cm (20pcs per box)



PACKAGING

1. Package (20 tables per lot): 325 × 440 × 550mm (L×W×H)
2. Master Dimension : 150 × 103 × 47mm (L×W×H)
3. Slave Dimension: Ø 68 × 18mm (D×H)



Inter-Register Communication (M) Sdn. Bhd. [198701004225 (162895-K)]

34, Jalan Tanjung SD 13/1, Bdr Sri Damansara, 52200 Kuala Lumpur.

Tel: (6)03-6272 8000 (8 Line)

Homepage: www.irc.com.my

Sales Person: Alex Wong - (6) 019-337 4781

E-mail: general@irc.com.my